

1. Identification

Product identifier	REDKEN QUICK BLOWOUT LIGHTWEIGHT BLOW DRY PRIMER SPRAY
Other means of identification	
SDS number	30-31-0000060
Recommended use	Personal care product used for cosmetic effect.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	

US Address: L'Oreal USA Products, Inc
133 Terminal Avenue
Clark, NJ 07066
USA

Canadian Address: L'Oreal Canada
4895 rue Hickmore
Ville St-Laurent, H4T 1K5
Canada

Emergency Phone # : 1-800-535-5053 (International: 352-323-3500)
In Canada - 1-613-996-6666 (Canutec (*666 Cellular))

For further Information: 1-732-499-2741

Poison Control # : 412-390-3326

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 1
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Causes serious eye damage.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
TRISILOXANE		107-51-7	10
ISODODECANE		13475-82-6	7.55
LACTIC ACID		50-21-5	3.38
GLYCERIN		56-81-5	2.25
ETHANOL		64-17-5	1.25

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up

Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Avoid discharge into drains, water courses or onto the ground.

Environmental precautions**7. Handling and storage****Precautions for safe handling**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
GLYCERIN (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
GLYCERIN (CAS 56-81-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value
ETHANOL (CAS 64-17-5)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
ETHANOL (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Applicable for industrial settings only. Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection	
Hand protection	Applicable for industrial settings only. Wear appropriate chemical resistant gloves.
Other	Applicable for industrial settings only. Wear appropriate chemical resistant clothing.
Respiratory protection	Applicable for industrial settings only. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Bi-Phase
Color	Not available.
Odor	Characteristic.
Odor threshold	Not available.
pH	2.9 - 3.5 (water phase)
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 212 °F (> 100 °C)
Flash point	104.0 °F (40.0 °C) Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1 - 1.04 g/cm ³ (water phase) 0.82 - 0.99 g/cm ³ (oil phase)
Explosive properties	Not explosive.
Fire point	< 212.00 °F (< 100.00 °C)
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye damage.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity Not known.

Product	Species	Test Results
---------	---------	--------------

REDKEN QUICK BLOWOUT LIGHTWEIGHT BLOW DRY PRIMER SPRAY

Acute

Dermal

ATEmix 12310 mg/kg

Oral

ATEmix 15200 mg/kg

Components	Species	Test Results
------------	---------	--------------

ETHANOL (CAS 64-17-5)

Acute

Dermal

LD50 Rabbit > 20000 mg/kg

Inhalation

Vapor

LC50 Rat 124.7 mg/l, 4 h OECD 403

Oral

LD50 Rat 10470 mg/kg OECD 401

GLYCERIN (CAS 56-81-5)

Acute

Dermal

LD50 Rabbit > 18700 mg/kg bw

Inhalation

LC50 Rat > 570 mg/L air, 1 h

Oral

LD50 Rat 27200 mg/kg bw

ISODODECANE (CAS 13475-82-6)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg OECD 402

Inhalation

Vapor

LC50 Rat > 5000 mg/m3, 8 h OECD 403

Components	Species	Test Results
Oral		
LD50	Rat	> 5000 mg/kg OECD 401
LACTIC ACID (CAS 50-21-5)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg EPA OPP 81-2
Inhalation		
<i>Mist</i>		
LC50	Rat	> 7.94 g/l, 4 h OECD 403
Oral		
LD50	Rat	3543 mg/kg EPA OPP 81-1
TRISILOXANE (CAS 107-51-7)		
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg bw
Inhalation		
LC50	Rat	> 22.6 mg/l, 4 h
Oral		
LD50	Rat	> 2000 mg/kg bw
Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible. No adverse effects due to skin contact are expected.	
Irritation Corrosion - Skin		
TRISILOXANE		OECD 401 Result: Not Irritating Species: Rabbit
ETHANOL		OECD 404 Result: Not Irritating Species: Rabbit
LACTIC ACID		OECD 404 Result: Severely Irritating Species: Rabbit
ISODODECANE		Result: Not Irritating Species: Human
GLYCERIN		Result: Not Irritating Species: Rabbit
Serious eye damage/eye irritation	Causes serious eye damage.	
Irritation Corrosion - Eye		
ETHANOL		OECD 405 Result: Irritating Species: Rabbit
ISODODECANE		OECD 405 Result: Not Irritating Species: Rabbit
LACTIC ACID		OECD 438 Result: Severely Irritating Species: ex vivo
TRISILOXANE		OPPTS 870.2400 Result: Not Irritating Species: Rabbit
GLYCERIN		Result: Not Irritating Species: Rabbit
Respiratory or skin sensitization		
Respiratory sensitization	Due to partial or complete lack of data the classification is not possible.	
Skin sensitization	Due to partial or complete lack of data the classification is not possible.	

Skin sensitization	
GLYCERIN	167 mg/m ³ air OECD 413, Inhalation Result: NOAEL Species: Rat Test Duration: 90 d
LACTIC ACID	EPA OPP 81-6 Result: Not Sensitizing Species: Guinea pig
ETHANOL	OECD 406 Result: Not Sensitizing Species: Guinea pig
ISODODECANE	OECD 406 Result: Not Sensitizing Species: Guinea pig
TRISILOXANE	OECD 406 Result: Not Sensitizing Species: Guinea pig
GLYCERIN	Result: Not Sensitizing Species: Guinea pig
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Mutagenicity	
ETHANOL	Result: In vitro and in vivo tests did not show mutagenic effects.
GLYCERIN	Result: In vitro and in vivo tests did not show mutagenic effects.
ISODODECANE	Result: In vitro and in vivo tests did not show mutagenic effects.
LACTIC ACID	Result: In vitro tests did not show mutagenic effects
Carcinogenicity	Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the classification is not possible.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Not listed.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)	
Not regulated.	
US. National Toxicology Program (NTP) Report on Carcinogens	
Not listed.	
Reproductive toxicity	Possible reproductive hazard.
Developmental effects	
ETHANOL	> 20000 ppm OECD 414, No effects on development Result: NOAEL Species: Rat
ISODODECANE	>= 2000 mg/kg bw/d OECD 414 Result: NOAEL Species: Rat
GLYCERIN	1310 mg/kg bw/d, No effects on development Result: NOAEL Species: Rat
TRISILOXANE	31 mg/l OECD 422, No effects on development Result: NOAEC Species: Rat
Reproductivity	
ISODODECANE	>= 3000 mg/kg bw/d OECD 415 Result: NOAEL Species: Rat
GLYCERIN	2000 mg/kg bw/d, No effects on fertility Result: NOAEL Species: Rat
ETHANOL	20700 mg/kg bw/d OECD 416, No effects on fertility Result: NOAEL Species: Rat
TRISILOXANE	31 mg/l OECD 422, No effects on fertility Result: NOAEC Species: Rat

Specific target organ toxicity - single exposure Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure Due to partial or complete lack of data the classification is not possible.

ISODODECANE	>= 5000 mg/kg bw/d OECD 408, Oral Result: NOAEL Species: Rat Test Duration: 90 d
ETHANOL	1730 mg/kg bw/d OECD 408, Oral Result: NOAEL Species: Rat
TRISILOXANE	25 - 250 mg/kg bw/d OECD 407 Result: NOAEL Species: Rat Test Duration: 28 d 7.74 mg/l OECD 422 Result: LOAEC Species: Rat 7.74 mg/l OECD 422, Inhalation Result: NOAEC Species: Rat
GLYCERIN	8000 mg/kg bw/d, Oral Result: NOAEL Species: Rat Test Duration: 2 yr

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Further information The reference to any animal testing for individual constituents mentioned in this document is based on public, third-party data.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
ETHANOL (CAS 64-17-5)			
Aquatic			
Acute			
Algae	EC50	Pseudokirchneriella subcapitata	22200 mg/l, 96 h
Crustacea	EC50	Ceriodaphnia dubia	5012 mg/l, 48 h
Fish	LC50	Pimephales promelas	15300 mg/l, 96 h
Other	IC50	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 3 h
Chronic			
Crustacea	NOEC	Daphnia magna	9.6 mg/l, 9 d
Fish	NOEC	Danio rerio	250 mg/l, 120 h OECD 212
GLYCERIN (CAS 56-81-5)			
Aquatic			
Acute			
Algae	EC0	Scenedesmus quadricauda	> 10000 mg/l, 192 h
Crustacea	EC50	Daphnia magna	1955 mg/l, 48 h
Fish	LC50	Oncorhynchus mykiss	54000 mg/l, 96 h
Other	NOEC	Pseudomonas putida	> 10000 mg/l, 16 h
ISODODECANE (CAS 13475-82-6)			
Aquatic			
Acute			
Algae	EL50	Pseudokirchneriella subcapitata	> 1000 mg/l, 72 h OECD 201
Crustacea	EL50	Daphnia magna	> 1000 mg/l, 48 h OECD 202
Fish	LL50	Oncorhynchus mykiss	> 1000 mg/l, 96 h OECD 203

Components		Species	Test Results
Other	EC50	Activated sludge of a predominantly domestic sewage	> 100 mg/l, 3 h OECD 209
<i>Chronic</i>			
Crustacea	NOAEL	Daphnia magna	1 mg/l, 21 d OECD 211
LACTIC ACID (CAS 50-21-5)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Pseudokirchneriella subcapitata	3500 mg/l, 72 h OECD 201
Crustacea	EC50	Daphnia magna	130 mg/l, 48 h OECD 202
Fish	LC50	Danio rerio	320 mg/l, 96 h OECD 203
Other	ED50	Activated sludge of a predominantly domestic sewage	> 100 mg/l, 3 h OECD 209
TRISILOXANE (CAS 107-51-7)			
Aquatic			
Algae		Pseudokirchneriella subcapitata	> 9.4 µg/l, 72 h
Crustacea		Daphnia magna	> 20 µg/l, 48 h
Fish		Oncorhynchus mykiss	> 19.4 µg/l, 96 h

Persistence and degradability

Biodegradability

Percent degradation (Aerobic biodegradation)

ETHANOL	84 % Result: Readily Biodegradable Test Duration: 20 d OECD 301
GLYCERIN	Result: Readily Biodegradable
ISODODECANE	20.6 % Result: Not Readily Biodegradable Test Duration: 28 d OECD 301 D
LACTIC ACID	Result: Readily Biodegradable
TRISILOXANE	0 % OECD 310 Result: Not Readily Biodegradable Test Duration: 28 d

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ETHANOL	-0.31
GLYCERIN	-1.76
ISODODECANE	6.4 6.96 QSAR
LACTIC ACID	-0.62 OECD 117

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT**FINISHED GOODS**

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE), Limited Quantity
Class	3
Packing group	III
Transport hazard class(es)	
Label(s)	Limited Quantity
Packaging exceptions	150
LTD QTY Net Inner Capacity	5.0 L

BULK

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE)
Class	3
Packing group	III
Transport hazard class(es)	
Label(s)	3
Special provisions	B1, B52, IB3, T4, TP1, TP29
Packaging non bulk	203

IATA**FINISHED GOODS**

UN number	ID8000
UN proper shipping name	CONSUMER COMMODITY
Class	9
Packing group	Not applicable.
ERG Number	9L

BULK

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE)
Class	3
Packing group	III
ERG Number	3L

IMDG**FINISHED GOODS**

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE), Limited Quantity
Class	3
Packing group	III
Environmental Hazards	
Marine pollutant	No.
Transport hazard class(es)	
Label(s)	Limited Quantity
EmS	F-E, <u>S</u> -E
LTD QTY Net Inner Capacity	5.0 L

BULK

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (TRISILOXANE, ISODODECANE)
Class	3
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, <u>S</u> -E

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHANOL (CAS 64-17-5)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical No (Exempt)**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

ETHANOL (CAS 64-17-5)

Low priority

GLYCERIN (CAS 56-81-5)

Other Flavoring Substances with OSHA PEL's

16. Other information, including date of preparation or last revision**Issue date** 04-17-2023**Version #** 01**NFPA ratings** Health: 3
Flammability: 2
Instability: 0**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.**Revision information** Physical & Chemical Properties: Multiple Properties