

1. Identification

Product identifier	REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER
Other means of identification	
SDS number	00-12-0000618
Recommended use	Personal care product used for cosmetic effect.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	

US Address: L'Oreal USA Products, Inc
133 Terminal Avenue
Clark, NJ 07066
USA

Canadian Address: L'Oreal Canada
4895 rue Hickmore
Ville St-Laurent, H4T 1K5
Canada

Emergency Phone # : 1-800-535-5053 (International: 352-323-3500)
In Canada - 1-613-996-6666 (Canutec (*666 Cellular))

For further Information: 1-732-499-2741

Poison Control # : 412-390-3326

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word Warning
Hazard statement Flammable liquid and vapor.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ETHANOL		64-17-5	20
MYRISTYL ALCOHOL		112-72-1	2

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Not available.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Use water spray to reduce vapors or divert vapor cloud drift. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
ETHANOL (CAS 64-17-5)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
ETHANOL (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Applicable for industrial settings only. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other Applicable for industrial settings only. Wear appropriate chemical resistant clothing.

Respiratory protection Applicable for industrial settings only. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Color Colorless.

Odor Characteristic.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range	> 95 °F (> 35 °C)
Flash point	93.2 °F (34.0 °C) Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No adverse effects due to eye contact are expected.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Not available.

Information on toxicological effects

Acute toxicity	Not known.
-----------------------	------------

Product	Species	Test Results
REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER		
<u>Acute</u>		
Oral		
ATEmix		540500 mg/kg

Components	Species	Test Results
ETHANOL (CAS 64-17-5)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 20000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	124.7 mg/l, 4 h OECD 403
Oral		
LD50	Rat	10470 mg/kg OECD 401
MYRISTYL ALCOHOL (CAS 112-72-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
<i>Dust</i>		
LC50	Rat	> 1.5 mg/l, 1 h
Oral		
LD50	Rat	> 2000 mg/kg OECD 401
Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible. No adverse effects due to skin contact are expected.	
Irritation Corrosion - Skin		
MYRISTYL ALCOHOL		OECD 404 Result: Not Irritating Species: Human
ETHANOL		OECD 404 Result: Not Irritating Species: Rabbit
Serious eye damage/eye irritation	Due to partial or complete lack of data the classification is not possible. No adverse effects due to eye contact are expected.	
Irritation Corrosion - Eye		
ETHANOL		OECD 405 Result: Irritating Species: Rabbit
MYRISTYL ALCOHOL		OECD 405 Result: Irritating Species: Rabbit
Respiratory or skin sensitization		
Respiratory sensitization	Due to partial or complete lack of data the classification is not possible.	
Skin sensitization	Due to partial or complete lack of data the classification is not possible.	
Skin sensitization		
ETHANOL		OECD 406 Result: Not Sensitizing Species: Guinea pig
MYRISTYL ALCOHOL		OECD 406 Result: Not Sensitizing Species: Guinea pig
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.	
Mutagenicity		
ETHANOL		Result: In vitro and in vivo tests did not show mutagenic effects.
MYRISTYL ALCOHOL		Result: In vitro and in vivo tests did not show mutagenic effects.
Carcinogenicity	Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the classification is not possible.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Possible reproductive hazard.**Developmental effects**

MYRISTYL ALCOHOL

> 2000 mg/kg bw/d OECD 422

Result: NOAEL

Species: Rat

ETHANOL

> 20000 ppm OECD 414, No effects on development

Result: NOAEL

Species: Rat

Reproductivity

MYRISTYL ALCOHOL

> 2000 mg/kg bw/d OECD 422, Based on test data for structurally similar materials.

Result: NOAEL

Species: Rat

ETHANOL

20700 mg/kg bw/d OECD 416, No effects on fertility

Result: NOAEL

Species: Rat

Specific target organ toxicity - single exposure Due to partial or complete lack of data the classification is not possible.**Specific target organ toxicity - repeated exposure** Due to partial or complete lack of data the classification is not possible.

ETHANOL

1730 mg/kg bw/d OECD 408, Oral

Result: NOAEL

Species: Rat

MYRISTYL ALCOHOL

3548 mg/kg bw/d OECD 408, Based on test data for structurally similar materials.

Result: NOAEL

Species: Rat

Test Duration: 90 d

Aspiration hazard Due to partial or complete lack of data the classification is not possible.**12. Ecological information****Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
ETHANOL (CAS 64-17-5)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Pseudokirchneriella subcapitata	22200 mg/l, 96 h
Crustacea	EC50	Ceriodaphnia dubia	5012 mg/l, 48 h
Fish	LC50	Pimephales promelas	15300 mg/l, 96 h
Other	IC50	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 3 h
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	9.6 mg/l, 9 d
Fish	NOEC	Danio rerio	250 mg/l, 120 h OECD 212
MYRISTYL ALCOHOL (CAS 112-72-1)			
Aquatic			
<i>Acute</i>			
Algae	EL50	Desmodesmus subspicatus	2.9 mg/l, 96 h OECD 201
Crustacea	EC50	Daphnia magna	3.2 mg/l, 96 h OECD 202
Fish	LC50	Oncorhynchus mykiss	> 1 mg/l, 96 h OECD 203
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	0.0016 mg/l, 21 d OECD 211

Persistence and degradability

Material name: REDKEN EXTREME BLEACH RECOVERY LAMELLAR WATER

1218122RK1 Version #: 01 Issue date: 09-12-2019

SDS US

6 / 9

Biodegradability**Percent degradation (Aerobic biodegradation)**

ETHANOL

84 %

Result: Readily Biodegradable

Test Duration: 20 d

MYRISTYL ALCOHOL

92 % ISO 10708

Result: Readily Biodegradable

Test Duration: 28 d

Bioaccumulative potential**Partition coefficient n-octanol / water (log Kow)**

ETHANOL

-0.31

MYRISTYL ALCOHOL

6.03

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations**Disposal instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

This product is ignitable (D001) RCRA hazardous wastes when intended for disposal.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information**DOT**

Materials associated with this document meet the criteria for US Department of Transportation exemption found at 49 CFR 173.150(g).

Packages containing limited quantities of retail products in volumes in accordance with the tables listed below maybe offered under the conditions of the exemption.

US Domestic Transportation

Per 49 CFR 173.150(g) exemptions:

	>70% Ethyl Alcohol (v/v) (w/w)			
	Inner Packaging	Net Contents	Gross Weight	Marking
Liquids	8 fl. oz.	192 fl. oz.	65 lbs.	None
	≤70% Ethyl Alcohol (v/v) (w/w)			
	Inner Packaging	Net Contents	Gross Weight	Marking
Liquids (glass)	8 fl. oz.	192 fl. oz.	65 lbs.	None
	16 fl. oz.	192 fl. oz.	65 lbs.	Contains Ethyl Alcohol
Liquids (non-glass)	16 fl. oz.	192 fl. oz.	65 lbs.	None
	1 gallon	192 fl. oz.	65 lbs.	Contains Ethyl Alcohol
General Conditions				
Inner packaging must be secured and cushioned within the outer package to prevent breakage, leakage and movement.				

DOT**FINISHED GOODS**

UN number UN1266
UN proper shipping name PERFUMERY PRODUCTS, Limited Quantity
Class 3
Packing group III
Transport hazard class(es)
Label(s) Limited Quantity
Packaging exceptions 150
LTD QTY Net Inner Capacity 5.0 L

BULK

UN number UN1266
UN proper shipping name PERFUMERY PRODUCTS, MARINE POLLUTANT (MYRISTYL ALCOHOL)
Class 3
Packing group III
Environmental hazards
Marine pollutant Yes

Transport hazard class(es)	
Label(s)	3
Special provisions	B1, IB3, T2, TP1
Packaging non bulk	203

IATA

FINISHED GOODS

UN number	ID8000
UN proper shipping name	CONSUMER COMMODITY
Class	9
Packing group	Not applicable.
ERG Number	9L

BULK

UN number	UN1266
UN proper shipping name	PERFUMERY PRODUCTS
Class	3
Packing group	III
Environmental hazards	
Marine pollutant	Yes
ERG Number	3L

IMDG

FINISHED GOODS

UN number	UN1266
UN proper shipping name	PERFUMERY PRODUCTS, Limited Quantity
Class	3
Packing group	III
Environmental Hazards	
Marine pollutant	No.
Transport hazard class(es)	
Label(s)	Limited Quantity
EmS	F-E, S-D
LTD QTY Net Inner Capacity	5.0 L

BULK

UN number	UN1266
UN proper shipping name	PERFUMERY PRODUCTS, MARINE POLLUTANT (MYRISTYL ALCOHOL)
Class	3
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, S-D

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHANOL (CAS 64-17-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical	Yes
--	-----

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

ETHANOL (CAS 64-17-5)

Low priority

16. Other information, including date of preparation or last revision**Issue date** 09-12-2019**Version #** 01**NFPA ratings** Health: 0
Flammability: 3
Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.